

MTP-25 & MTP-85



Bluetooth Printer



2" Bluetooth Thermal Printer



3" Bluetooth Thermal Printer



USB



Bluetooth



Android

BILL PRINTING
FANTASY
4

- 1 Small & comfortable to carry
- 2 Easy paper loading & User friendly with classic three-button
- 3 USB + Bluetooth interface (standard) + Android
- 4 LED indication facility available during abnormal condition of printer

SPECIFICATIONS OF WePMTP-25 & MTP-85



2" Bluetooth Thermal Printer

3" Bluetooth Thermal Printer

Features of MTP-25

- Drop in paper loading, easy operation
- Support to print receipt during charging the battery
- **Bluetooth** : BT3.0 and BLE4.0
- Support 1D barcode, QR barcode
- Support for printing different density bitmap and download graphics
- **Print Method** : Direct thermal line
- **Dot Density** : 384 dots/line
- **Print Speed** : 60mm/s (Max)
- **Interface** : USB+Bluetooth (Standard) +Android
- **Paper Width** : 58mm
- **Paper Diameter** : 50mm
- **Print Commands** : Compatible with ESC/POS
- **Barcode Type** : UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39, CODABAR, ITF, CODE93, CODE128, QR Code
- **Buffer** : Input buffer 4K bytes NV Flash 60K bytes
- **Dimension** : 148.5(L) X 86(W) X 58.5(H)mm
- **Weight (including battery)** : 288g
- **Power Adaptor** : Input - AC100-220V; Output - DC9V/1A
- **Battery** : 1800mAh, 7.4V rechargeable Li-ion Battery
- **Charging Time** : 2.5~3.5 hours
- **Work Environment** : Temperature: 0 ~ 45°C; Humidity: 10 ~ 80%
- **Storage Environment** : Temperature: 10 ~ 60°C; Humidity: 10 ~ 90%
- **Thermal Mechanism** : 50KM

Features of MTP-85

- Drop in paper loading, easy operation.
- Support to print receipt during charging the battery.
- **Bluetooth** : BT3.0 and BLE4.0
- Support 1D barcode, QR barcode
- Support for printing different density bitmap and download graphics
- **Print Method** : Direct thermal line
- **Dot Density** : 576 dots/line
- **Print Speed** : 60mm/s (Max)
- **Interface** : USB+Bluetooth (Standard) +Android
- **Paper Width** : 80mm
- **Paper Diameter** : 50mm
- **Print Commands** : Compatible with ESC/POS
- **Barcode Type** : UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39, CODABAR, ITF, CODE93, CODE128, QR Code
- **Buffer** : Input buffer 4K bytes NV Flash 60K bytes
- **Dimension** : 131(L) X 107(W) X 58(H)mm
- **Weight (including battery)** : 350g
- **Power Adaptor** : Input - AC100-220V; Output - DC9V/1A
- **Battery** : 2200mAh, 7.4V rechargeable Li-ion Battery
- **Charging Time** : 3.0~5.0 hours
- **Work Environment** : Temperature: 0 ~ 45°C; Humidity: 10 ~ 90%
- **Storage Environment** : Temperature: 10 ~ 50°C; Humidity: 10 ~ 90%
- **Thermal Mechanism** : 50KM



Dear Valued Customer,

Let us protect our environment. Help us in safe disposal of Ewastes generated by our products. Dispose all defective and end of life parts and products to our authorized Ewaste collection points or collection centers. For more details, Visit: www.wepindia.com or Call: 1800 425 9494



Dealer Name and Address



Version-1.0/Nov/2016